

# Self Retracting Lifeline



21430

## Features

- Lightweight
- Ergonomic shape for easy handling
- Safe
- Rubber stop which acts as a buffer if the cable is accidentally released
- Side carrying handles on 50 and 100 ft. models allows for easy transportation
- Dual locking pawls and a constant triggering speed allow great work versatility, regardless of position
- In the event of a fall the sudden jerk in the wire rope will activate the centrifugal locking mechanism within 2 feet (0.6 m)
- Fall indicating device at swivel snap hook connector allows for a visual indication of deployment
- Corrosion resistant
- The wire rope in the housing automatically adjusts its length, taking up the slack minimizing the free fall distance should a fall occur
- No annual recertification required

## Standards

- Meets and or exceeds:
- CSA Z259.2.2-04 Type 2
  - ANSI Z359.1
  - OSHA Fall protection requirements

Model number:	21430	21450	21500
Length	30 ft.	50 ft.	100 ft.
Wire rope	Wire rope 3/8 in. galvanized steel	Wire rope 3/8 in. galvanized steel	Wire rope 3/8 in. galvanized steel
Wire rope breaking strength	3300 lbs	3300 lbs	3300 lbs
Max arresting force	900 lbs (4 kN)	900 lbs (4 kN)	900 lbs (4 kN)
Maximum fall arrest distance	24 in (2 ft.)	24 in (2 ft.)	24 in (2 ft.)
Capacity:	310 lbs (140 kg)	310 lbs (140 kg)	310 lbs (140 kg)



3160, de Rouen  
Montréal (Québec)  
H1W 1K7  
www.jelco.ca

Tel.: 514 522-6038  
Toll Free.: 1 800 361-4583  
Fax: 514 521-7138  
sales@jelco-alubox.com

www.jelco.ca

